




Infill cover with T-frames



Type DI2612C shown

Product Table

Type	Part No.	Clear Opening Width (A)	Clear Opening Length (B)	Overall Width (C)	Overall Length (D)	Overall Depth (E)	Cover Width (F)	Cover Length (G)	Cover Weight (kg)	Overall Weight (kg)
DI249C	142355	450	955	622	1124	85	520	1010	30/30	107
DI2612C	142356	600	1255	772	1424	85	670	1310	56/56	170
DI2912C	142357	900	1255	1072	1424	85	970	1310	75/75	217
DI2915C	143171	900	1555	1072	1724	85	970	1610	75/102	252
DI2918C	142358	900	1855	1072	2024	85	970	1910	102/102	287

Notes:

1. All dimensions in the table are nominal and are shown in millimeters.
2. Decorative Brass (BE) or Stainless Steel (SS) edging can be added - just specify BE or SS and height (12mm or 40mm) after part no.
3. Bolts are standard for each cover, specify Standard Locking bolts (SL) or security rated Security Bolts (SB) after part no.
4. If structural locking bolts are required, contact ACO.

ACO Specification Information

ACO ACCESS

Rhinocast - 2-part infill iron access cover with T-frames - Class C

Accessories

Part No.	Description	Weight (kg)
84654	Rhinocast short handle lifters (pair)	3.60
84854	Rhinocast long handle lifters (pair)	8.10
73131	Sealing grease	4.40
84620	Rectangular red caps (short) for lifting key holes	-
84626	Circular red caps for locking bolt holes	-
77416	Brass plate (75 x 75mm) marked 'ELECTRICITY'	0.05
77402	Brass plate (75 x 75mm) marked 'COMMUNICATIONS'	0.05
77420	Brass plate (75 x 75mm) marked 'GAS'	0.05

Specifications

General

The access covers and frames shall be ACO Rhinocast infill access covers with T-frames as manufactured by ACO Pty Ltd. or equal approved.

Materials

The Rhinocast infill access covers and T-frames shall be manufactured from ductile iron (spheroidal graphite cast iron) to the requirements of AS 3996 with:

Minimum tensile strength: 600MPa
Minimum elongation: 3%

The cover and frames shall be coated with a black water based paint for short term protection only.

Cover

The Rhinocast infill covers with reduced ribs allow for 40mm deep pavers shall have the following features to AS 3996 requirements:

Load Class C (150kN)
Watertight & Gas-tight Sealed
Internal Pressure Resistance IPD
Permanent Markings
Lifting Keyholes

Rhinocast covers are locked down as standard with two stainless steel M12x75 hex head bolts.

Optional, specify if required:
For a more secure cover, specify 'SB' after part number for tamper resistant security bolts.

Optional, specify if required:


For pavers deeper than 40mm, specify SS / BE* for stainless steel or brass edging, and specify 12mm / 40mm* high edging after the part number.

Installation

The access cover shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as applicable

Rebate Dimensions For Class C



Due to the varying frame dimensions for different covers and decorative edging options, dimensions shown indicate the minimum amount of concrete required around the frame.

Full details at www.acoaccess.com.au/product-support/installation-guidance/

Concrete of a minimum strength of 32MPa and minimum aggregate of 12mm is recommended.



**ACO Pty Ltd
Australia**

Ph: 1300 765 226
www.acoaus.com.au



© January, 2025 ACO Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.